



#### For use in:

Dimensional Gaging and Metrology  
Medical & Automotive Test Stands  
Surface/Web Profiling  
Factory Automation  
Material Testing

# LAS-19-R Series

## Spring-Loaded AC-LVDTs

Ideal for Applications with a Tight Fit



The LAS-19-R series AC-LVDT (Linear Variable Differential Transformer) linear position sensors by H.G. Schaevitz LLC *dba* Alliance Sensors Group are spring-loaded, hermetically-sealed, contactless devices designed for industrial and commercial applications, such as: factory automation, metal and paper mills, valve position, robotic assembly systems, pharmaceutical and food processing, and outdoor or wet environment applications. This ruggedized linear device has excellent price-to-performance and stroke-to-length ratios, making the LAS-19-R sensors ideal for use in power generation and industrial automation equipment, and in many OEM positioning applications.

LAS-19-R series AC-LVDTs are offered in 6 ranges from  $\pm 0.050$  to  $\pm 2.00$  inches ( $\pm 1.27$  to  $\pm 50$  mm) with excellent linearity and infinite resolution. LAS-19-R series AC-LVDTs operate from a nominal 3 Vrms, 2.5 to 3.3 kHz excitation source. They are packaged in a 0.750 inch (19.0 mm) OD hermetically-sealed stainless steel housing with a 1/2-20 UNF thread and two hex jam nuts, a 0.210 inch diameter (5.3 mm) probe with an AGD No 9 contact tip, and a PTO2-10-6P (6-pin) radial connector.

When mated with ASG's industrial AC-LVDT DIN-rail-mountable signal conditioner, an LAS-19-R series AC-LVDT becomes part of a complete measurement solution.

ASG's AC-LVDTs are also offered in other body and range versions, including the LA-9.5, LA-19, LA-20.6, LA-21, LA-25, and LA-27.

#### Features:

- Spring-loaded AC-LVDT with radial connector
- Hermetically-sealed 0.750 inch OD stainless steel housing
- 1/2-20 UNF mounting threads with nuts
- Radial PTO2-10-6P Connector

#### Electrical Specifications:

Available Ranges:	$\pm 0.050"$ , $0.125"$ , $0.250"$ , $0.500"$ , $1.0"$ , and $2.0"$
Excitation Frequency:	2.5 to 3.3 kHz
Excitation Voltage:	3 V ACrms nominal
Linearity Error:	$\leq \pm 0.25\%$ of FSO (typical 0.15%)
Null Voltage:	$< 0.05\%$ of FSO
Operating Temperature:	-55 to 125 C
Operating Coefficient:	$< -0.02\%$ FSO/K
Humidity:	95% RH, non-condensing
Shock:	1000 g, 11 msec.
Vibration:	20 g to 2 kHz

**ALLIANCE SENSORS GROUP**  
A DIVISION OF H.G. SCHAEVITZ LLC


# LAS-19-R Series

## Ordering Information:

Series Name	Body Diameter, mm (XX)	Termination Topology (X)	Bipolar Range, Inches (XX)	I/O Connection (XX)
LAS	19 - 19 mm (0.75 inch)	R - Radial	0.05 - +/- .050 inches	02 - PT02-10-6P (6-pin)
			0.125 - +/- .125 inches	
			0.25 - +/- .250 inches	
			0.5 - +/- .500 inches	
			01 - +/- 1.0 inches	
			02 - +/- 2.0 inches	

PT02-10-6P Connector	
Pin	I/O Function
A	Secondary 1
B	Secondary 1*
C	Secondary 2*
D	Secondary 2
E	Primary
F	Primary

\*Connect pin B to pin C for differential secondary output



Nominal Range	Sensitivity	Primary Z	Length A	Length B	Length C	Pretravel	Overtravel	Weight
inches [mm]	mV/V/.001in [mm]	Ohms	inches [mm]	inches [mm]	inches [mm]	inches [mm]	inches [mm]	oz. [grams]
±0.050 [1.3]	6.10 [240]	325	4.61 [117]	3.51 [89]	1.97 [50]	0.12 [3.0]	0.12 [3.0]	2.89 [82]
±0.125 [3.0]	3.90 [153]	735	5.26 [134]	4.15 [105]	2.60 [66]	0.13 [3.3]	0.13 [3.3]	3.39 [96]
±0.250 [6.3]	2.50 [98]	1400	6.02 [153]	4.91 [125]	3.35 [85]	0.10 [2.5]	0.10 [2.5]	4.00 [113]
±0.500 [12.5]	0.65 [26]	1200	10.54 [268]	9.05 [230]	5.88 [149]	0.10 [2.5]	0.10 [2.5]	6.00 [170]
±1.000 [25]	0.61 [24]	1250	12.81 [322]	10.51 [267]	7.34 [186]	0.05 [1.3]	0.05 [1.3]	6.31 [179]
±2.000 [50]	0.37 [14]	2150	20.91 [531]	16.35 [415]	10.87 [276]	0.02 [0.5]	0.02 [0.5]	10.23 [290]

**ALLIANCE SENSORS GROUP**  
A DIVISION OF H.G. SCHAEVITZ LLC

Alliance Sensors Group  
102 Commerce Drive, Unit 8  
Moorestown, New Jersey 08057 USA  
Ph: 856-727-0250  
www.alliancesensors.com  
info@alliancesensors.com

All specifications are subject to change without notice.

© Alliance Sensors Group, 2021

V2.0 Rev. 09/2021